



800-472-6703 **www.ricelake.com**

Ready-n-Weigh Bench Scale Package

CW-90B SCALE BASE AND 480/480 LEGEND PLUS INDICATOR



1 INDICATOR

480 Legend or 480 Legend Plus with numeric keypad Enclosure is NEMA Type 4X/IP66, heavy-gauge stainless steel LED display



2 SCALE BUILD

12-inch column
Removable top cover for easy cleaning

Rubber feet for exceptional traction while avoiding scratches



3 LOAD CELL

IP67 aluminum environmentally sealed load cell



IP67 aluminum, environmentally sealed

The CW-90B Ready-n-Weigh bench scale system is a complete bench scale, column and indicator package. Pair the CW-90B IP67 rated platform with the 480 Legend indicator or choose the 480 Legend Plus for a full numeric keypad. Both indicators come with an IP66 rated stainless steel enclosure.

Capacity	Base Size
5 lb x 0.001 lb/2.5 kg x 0.0005 kg	10 x 10 x 4.25 in
10 lb x 0.002 lb/5 kg x 0.001 kg	10 x 10 x 4.25 in
25 lb x 0.005 lb/10 kg x 0.002 kg	10 x 10 x 4.25 in
25 lb x 0.005 lb/10 kg x 0.002 kg	12 x 12 x 4.25 in
50 lb x 0.01 lb/25 kg x 0.005 kg	12 x 12 x 4.25 in
100 lb x 0.02 lb/50 kg x 0.01 kg	12 x 12 x 4.25 in

STANDARD FEATURES

- Package includes scale with IP67 aluminum environmentally sealed load cell with an indicator and 12-inch column
- Factory calibrated, with indicator setup and configured for 5,000 divisions
- Scale includes rubber feet to provide exceptional traction and avoid scratching surfaces along with removable top cover for ease of cleaning
- AC Power 100-240VAC
- LED display, 0.8 in, six-digit, seven-segment
- · Battery backed time and date
- Two independent serial ports, RS-232 and 20mA for connecting to a variety of peripherals

CW-90B SPECIFICATIONS

LOAD CELL, NTEP CERTIFIED: SCALE CONSTRUCTION: MAXIMUM OVERLOAD:

MAXIMUM OVERLOAD: 180 to 200% depending on capacity
OVERLOAD PROTECTION: Five-point, independently adjusted
CABLE LENGTH: 34 in

COMPENSATED
TEMPERATURE RANGE:
WARRANTY:

AANGE: 14° F to 104° F (-10° C to 40° C) Two-year limited warranty

304 stainless steel

APPROVALS







NTEP CC 95-072 AM-5092, Class III 5,000 D Class III 5,000 D

480/480 LEGEND PLUS SPECIFICATIONS

POWER: Line voltages: 110 - 240 VAC

FREQUENCY: 50 or 60 Hz

DISPLAY: 0.8 in (20 mm), LED, 6-digit, 7-segment display

KEYS/BUTTONS: 480 Plus

Power, Gross/Net, Menu, Unit, Tare, Print, Zero and numeric keypad

480

Power, Gross/Net, Menu, Unit, Tare, Print, Zero

RATING/MATERIAL: Enclosure: NEMA Type 4X/IP66, stainless steel, washdown

WARRANTY: Two-year limited warranty

APPROVALS











SALES AND TECHNICAL ASSISTANCE



HEADQUARTERS

230 West Coleman Street Rice Lake, Wisconsin 54868 - USA Tel: (715) 234 9171 | Fax: (715) 234 6967 www.ricelake.com