

Ready-n-Weigh Bench Scale Package

CW-90B SCALE BASE AND
482/482 LEGEND® PLUS INDICATOR



RICE LAKE[®]
WEIGHING SYSTEMS

800-472-6703

www.ricelake.com

Ready-n-Weigh Bench Scale Package

CW-90B SCALE BASE AND 482/482 LEGEND® PLUS INDICATOR



1 INDICATOR

482 Legend or 482 Legend Plus with numeric keypad
Enclosure is NEMA Type 4X/IP66, heavy-gauge stainless steel
LCD display

2 SCALE BUILD

12-inch column
Removable top cover for easy cleaning
Rubber feet for exceptional traction while avoiding scratches

3 LOAD CELL

IP67 aluminum environmentally sealed load cell

The CW-90B Ready-n-Weigh bench scale system is a complete bench scale, column and indicator package. Pair the CW-90B IP67 rated platform with the 482 Legend indicator or choose the 482 Legend Plus for a full numeric keypad. This package is also offered with an internal battery, making it perfect for applications that require a portable bench scale.

Capacity	Base Size
5 lb x 0.001lb/2.5 kg x 0.0005 kg	10 x 10 x 4.25 in
10 lb x 0.002 lb/5 kg x 0.001kg	10 x 10 x 4.25 in
25 lb x 0.005 lb/10 kg x 0.002 kg	10 x 10 x 4.25 in
25 lb x 0.005 lb/10 kg x 0.002 kg	12 x 12 x 4.25 in
50 lb x 0.01lb/25 kg x 0.005 kg	12 x 12 x 4.25 in
100 lb x 0.02 lb/50 kg x 0.01kg	12 x 12 x 4.25 in

STANDARD FEATURES

- Package includes scale with IP67 aluminum environmentally sealed load cell with an indicator and 12-inch column
- Factory calibrated, with indicator setup and configured for 5,000 divisions
- Scale includes rubber feet to provide exceptional traction and avoid scratching surfaces along with removable top cover for ease of cleaning
- LCD, 0.8in six-digit, seven-segment backlit display
- Battery backed time and date
- Two independent serial ports, RS-232 and 20mA for connecting to a variety of peripherals

CW-90B SPECIFICATIONS

LOAD CELL, NTEP CERTIFIED:	IP67 aluminum, environmentally sealed
SCALE CONSTRUCTION:	304 stainless steel
MAXIMUM OVERLOAD:	180 to 200% depending on capacity
OVERLOAD PROTECTION:	Five-point, independently adjusted
CABLE LENGTH:	34 in
COMPENSATED TEMPERATURE RANGE:	14° F to 104° F (-10° C to 40° C)
WARRANTY:	Two-year limited

APPROVALS:



482/482 LEGEND PLUS SPECIFICATIONS

POWER:	Line voltages: 110 - 240 VAC Frequency: 50 or 60 Hz
DISPLAY:	0.8 in (20 mm), LCD, 6-digit, 7-segment display
INTERNAL BATTERY:	Rechargeable Lithium-Ion
ESTIMATED BATTERY LIFE:	40 hours (350W load without backlight), 15 hours (350W load with backlight)
APPROX. CHARGE TIME:	16 hours to achieve 100%
KEYS/BUTTONS:	482 Plus Power, Gross/Net, Menu, Unit, Tare, Print, Zero and numeric keypad 482 Power, Gross/Net, Menu, Unit, Tare, Print, Zero
RATING/MATERIAL:	Enclosure: NEMA Type 4X/IP66, stainless steel, washdown
WARRANTY:	Two-year limited

APPROVALS



SALES AND TECHNICAL ASSISTANCE

RICE LAKE®
WEIGHING SYSTEMS

HEADQUARTERS
230 West Coleman Street
Rice Lake, Wisconsin 54868 - USA
Tel: (715) 234 9171 | Fax: (715) 234 6967
www.ricelake.com